

形式 Type	所需馬力 Motor		使用壓力 Pressure	流量與位量 Displacement		迴轉數 R.P.M.	空氣槽 Air tank			概略尺寸 Approx. Dimensions			
	HP	KW		kg/cm²	理論值 m³/min		實際值 m³/min	mm x Lmm	m³	No.	高度	寬度	高度
			L mm								W mm	H mm	Weight kg
HV-50S	50	37	35	5.15	3.6	250	490 x 1525	0.3	1	3800	1850	2400	3920
HV-60S	60	45	35	6.38	4.4	310	490 x 1525	0.3	1	3800	1850	2400	3920
HV-75S	75	56	35	7	4.9	340	490 x 1525	0.3	2	3800	1850	2400	4000
HV-100S	100	75	35	9.5	6.66	260	490 x 1525	0.3	2	4300	2000	2400	4700
HV-125S	125	90	35	11.7	8.2	320	490 x 1525	0.3	2	4300	2000	2400	4770
HV-150S	150	110	35	15.1	10.6	290	490 x 1525	0.3	2	5700	2100	2500	6750
HV-175S	175	130	35	17.5	12.2	305	490 x 1525	0.3	2	5700	2100	2500	6820
HV-200S	200	150	35	19.1	13.4	367	490 x 1525	0.3	2	5700	2100	2500	6980